

POPPY STAR

Bartoli Design / 2006

segls

Stacking armchair

Frame: air moulded injection of polypropylene, reinforced with fiber glass. The injection material is coloured in bulk and allows a satin finish

Outdoor version: with a drainage hole in the seat.


Feet: in thermoplastic material



	Article	Finish	pcs / dimensions volume / gross weight product net weight
Armchair	S0400	Polypropylene	4 pcs / 57x74x98 cm 0,41 m ³ / 18,5 Kg 3,75 Kg
	S0400	Fire-retardant polypropylene colour grey 7V	
	S0400 E	Polypropylene Outdoor version with drainage hole	

Finishes


Polypropylene



Fire-retardant Polypropylene



Dimensions



Accessories

Kart Universal trolley (art.C0514)

Note

Attention: standard packing unit 4 pcs of the same colour

Fire retardant certifications

The product meets Class 2 by the Italian Minister of Interior.

Resistance tests

UNI-EN 1022/98 - stability
EN 1728/00 - leg forward static load test
EN 1728/00 - leg sideways static load test
EN 1728/00 - seat impact test
EN 1728/00 - back impact test
EN 1728/00 - seat front edge durability test
EN 1728/00 - seat and back fatigue test
EN 1728/00 - seat and back static load test
EN 1728/00 - arm downwards static load test
EN 1728/00 - arm sideways static load test
EN 1728/00 - arm fatigue test
ANSI-BIFMA 5.1-2002/06 - backrest strenght test - static
ANSI-BIFMA 5.1-2002/11 - seat durability test - cyclic
ANSI-BIFMA 5.1-2002/12 - stability test
ANSI-BIFMA 5.1-2002/13 - arm strenght test- vertical static
ANSI-BIFMA 5.1-2002/14 - arm strenght - horizontal static
ANSI-BIFMA 5.1-2002/16 - back durability test - cyclic
ANSI-BIFMA 5.1-2002/18 - Leg strenght test - side application